

## Mulgara - Feature #173

### Implement Accept headers

11/22/2008 03:03 PM - Paula Gearon

|  |                     |                        |           |
|--|---------------------|------------------------|-----------|
| <b>Status:</b>   | Closed              | <b>Start date:</b>     |           |
| <b>Priority:</b>   | High                | <b>Due date:</b>       |           |
| <b>Assignee:</b>   | Paula Gearon        | <b>% Done:</b>         | 0%        |
| <b>Category:</b>   | HTTP interface      | <b>Estimated time:</b> | 0.00 hour |
| <b>Target version:</b>   | General development |                        |           |
| <b>Resolution:</b>   | fixed               |                        |           |
| <b>Description</b>   |                     |                        |           |
| <p>The web api current takes "out" as a parameter to define the return type. This should be implemented as a content type defined in the Accept header from the client. See:<br/><a href="http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.1">http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.1</a></p> <p>For ease of access with clients that set their own Accept types, the "out" parameter should continue to be accepted, but the name should change to something more sensible, like "type".</p> |                     |                        |           |

### History

---

#### #1 - 02/10/2009 12:13 AM - Paula Gearon

- Status changed from New to Closed
- Resolution set to fixed

Implemented. Also, changed parameter name to "format", and this overrides the Accept header.

#### #2 - 02/10/2009 01:56 PM - ronald -

Merged into trunk in [r1457](#).