Mulgara - Feature #71

Clean up DatabaseOperationContext

Mulgara

09/13/2007 08:57 AM - Andrae Muys -

Status: New Start date:

Priority: Normal Due date:

Assignee: Andrae Muys - % Done: 0%

Estimated time:

0.00 hour

Target version:

Resolution:

Category:

```
Description
This is the next cleanup refactoring.
<br/>
<br/>
We have:
<br/>
<br/>
[[ResolverFactory]] findModelResolverFactory(long model)
<br/>
[[ResolverFactory]] findUncachedExternalResolverFactory(long model)
<br/>
[[ResolverFactory]] findModelTypeResolverFactory(URI modelTypeURI)
<br/>
Resolver obtainResolver(ResolverFactory resolverFactory)
<br/>
URI mapToModelTypeURI(URI modelURL)
<br/>
URI findModelTypeURI(long model)
<br/>
String findProtocol(long n)
<br/>
most of which do multiple overlapping tasks, often implemented slightly differently.
<br/>
<br/>
Most of these methods used to live in different classes, and have migrated here as their homes wer
e refactored and tidied.
<br/>
```


[[DatabaseOperationContext]] and [[LocalQueryResolver]] are the last two dumping grounds in the sy stem-core where we have left the cruft that was too difficult to clean up concurrently with previous refactorings; and [[DatabaseOperationContext]] is by far the worst of the two - so it's next on the list.

04/09/2024 1/1